



## 236 e-series

Husqvarna 236 e-series is ideal for jobs like pruning, lighter cutting tasks and hobby work. Easy to start and operate with built-in Husqvarna features like ergonomic design, facilitating technology and powerful X-Torq® engine with low emissions. Equipped with Smart Start® and tool-less chain tensioning.




### X-TORQ®

Delivers lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



### AIR INJECTION

Extends the interval between filter cleaning, improving efficiency and increases engine life.



### COMBINED CHOKE/STOP CONTROL

Combined choke/stop control allows for easier starting and reduces the risk of the engine flooding.



### TWO MASS PRINCIPLE

Effectively minimising vibrations by isolating the engine from the handles reducing operator fatigue.

## Features

- Tool less chain tensioner
- Smart Start® for easy starting
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

## Technical data

Cylinder displacement	2.3 cu.inch / 38.2 cm <sup>3</sup>
Power output	1.9 hp / 1.4 kW
Maximum power speed	9000 rpm
Idling speed	3000 rpm
Spark plug	NGK BPMR7A, Champion RCJ7Y
Electrode gap	0.02" / 0.5 mm
Oil tank volume	0.09 US pint / 0.2 litre
Oil pump type	Fixed flow
Equivalent vibration level (ahv, eq) front / rear handle	2.1/2.7 m/s <sup>2</sup>
Sound pressure level at operators ear	100.7 dB(A)
Sound power level, guaranteed (LWA)	113 dB(A)
Chain pitch	3/8" LP
Recommended bar length, min-max	13"-16" / 33-40 cm
Chain speed at max power	53.48 fts / 16.3 m/s
Weight (excl. cutting equipment)	10.3 lbs / 4.7 kg

### ARTICLES

966 64 04-03	14" - 3/8 - SN - AS - AU, NZ	\$ 369.00
--------------	------------------------------	-----------

